



SUBMITTAL
Classic No-Hub COUPLINGS

DATE

Architect

Project

Contractor

Engineer

Classic No-Hub™ Couplings are engineered to connect hub-less cast iron pipe and fittings. The coupling sealing sleeve or gasket is manufactured from a properly vulcanized virgin compound where the primary elastomer is polychloroprene (neoprene). The gasket is housed inside a 301 stainless steel corrugated shield. The shield is 0.007" thick. Depending on the size of the shield, two or four 301 stainless steel clamps encircle the shield and provide the sealing force. The 5/16" hex-head screws are manufactured with 305 grade stainless steel. The couplings are available in sizes ranging from 1 1/2" – 10". The couplings are designed for an installation torque of 60 in-lbs. The entire coupling is corrosion resistant. The couplings are NSF® Certified* and are in full compliance to CISPI 310, ASTM C1277 and ASTM C564.

*Sizes 1/2" through 10" only.

Sizes 1 1/2", 2", 3", and 4" consist of a 2 1/8" wide corrugated 301 stainless steel shield with two stainless steel clamps mounted in a series and secured with fixed and floating eyelets to allow the clamp to travel during tightening.

Sizes 5" and 6" consist of a 3" wide corrugated 301 stainless steel shield with four clamps.

Sizes 8" and 10" consist of a 4" wide corrugated 301 stainless steel shield with four stainless steel clamps.

Size	Part No.	Installation Torque Inch Pounds	No. of Clamps Per Coupling
1 1/2"	621708G	60	2
2"	621808G	60	2
3"	621908G	60	2
4"	622008G	60	2
5"	622108G	60	4
6"	622208G	60	4
8"	622308G	60	4
10"	623008G	60	4
2" X 1 1/2"	62R218G	60	2
3" x 2"	62R328G	60	2
4" x 3"	62R438G	60	2

MATERIALS	
Band & Housing	Type 301 AISI stainless steel
Screw	Type 305 AISI stainless steel 5/16" hex head
Shield	Type 301 AISI stainless steel, corrugated, thickness 0.007"
Gasket	The gasket is fabricated from a properly vulcanized virgin compound in compliance to ASTM C 564.

Country of Origin - Mexico