



DATE: \_\_\_\_\_

ARCHITECT: \_\_\_\_\_ PROJECT: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_ ENGINEER: \_\_\_\_\_

# SUPER HEAVY-DUTY GREEN SHIELD® NO-HUB COUPLINGS SUBMITTAL



The Ideal Tridon Super Heavy-Duty Green Shield® couplings are a quality line of heavy-duty no-hub cast iron pipe couplings **made in the USA**. They are engineered to replace the less-efficient hub and spigot connection and are designed to be used where structural reinforcement and higher sealing pressures are required. Compared to standard duty couplings, the Super Heavy-Duty “HD” couplings have a wider footprint on the joint, allowing an increased number of higher torque capacity clamps to add a measure of structural rigidity and enhanced sealing pressure capabilities for applications requiring higher safety margins against leakage. The coupling consists of an elastomeric gasket, housed inside a stainless steel bi-directional corrugated shield and clamped with heavy-duty stainless steel clamps. Sizes are available in a range of 1½” – 10”, and are designed for both above and below grade installation, and in temperature environments from -30°F to 220°F. The all 300 series stainless steel construction ensures complete corrosion resistance while exceeding all ASTM C1540 test requirements.

*Ideal Tridon's green shields are registered in the U.S. Patent and Trademark Office.*

## FIND YOUR PART NUMBER

Size (pipe diameter)	Part Number	Number of Clamps	Coupling Width	Installation Torque	Screw Hex Size
1 ½"	6217H8G	4	3"	80 inch-pounds (all sizes)	3/8" (all sizes)
2"	6218H8G				
3"	6219H8G				
4"	6220H8G				
5"	6221H8G	6	4"		
6"	6222H8G				
8"	6223H8G				
10"	6230H8G				

## MATERIALS

Components	All Compliant to ASTM C1540
Clamp	All 300 Series AISI Stainless Steel (Band and Screw Housing)
Screw	All 300 Series AISI Stainless Steel (3/8" Hex Head / Shoulder)
Shield	All 300 Series AISI Stainless Steel
Rivets	All 300 Series AISI Stainless Steel
Gasket	Elastomeric Compound Primarily Consisting of Neoprene; Meets ALL Requirements of ASTM C564

### THE SHIELD

The 0.008" thick, all 300 grade stainless steel green shield requires less band-load to transfer pressure to the gasket, leaving more clamping load in reserve to compress the gasket. The bi-directional corrugations create clamp sealing pressure in both parallel and transverse directions on the gasket and pipe, thereby avoiding pull-out failures, and providing a positive, reliable seal.

### THE CLAMPS

Heavy-duty clamps with all 300 series stainless steel construction, featuring 9/16" wide bands and 3/8" hex head screws, provide optimum sealing force at an 80 inch-pound installation torque.



Coupling Meets ASTM C1540	UPC ®	Meets FM1680
Gasket Meets ASTM C564	IAPMO Listed File # 3198	Meets CSA B602
		Meets Sealing Requirements Independent Lab Certified

### THE GASKET

Made from high-quality elastomeric compound per ASTM C564, the Ideal Tridon no-hub gasket features a laterally-spaced pattern of multiple thick sealing sectors and adjacent groove sectors. When the clamps are tightened, this pattern permits the clamping bands and the shield to form a restriction, impeding the movement of the shield relative to the gasket.


## GASKET PERFORMANCE

Specific material composition requirements, workmanship, and physical testing of mechanical properties of the rubber sealing gasket have been established by ASTM C564 to ensure the prevention of damage caused by the wide varieties of environmental exposure that no-hub coupling products may experience. The specification requires all gaskets to be manufactured from a properly vulcanized virgin compound in which the primary elastomer is Neoprene. The proper blend of rubber elastomers have proven effective in these gaskets maintaining their sealing properties throughout hot and cold conditions, ozone, chemical, and solvent exposure, along with the physical strength to resist damage from physical stresses such as foundation settling or other naturally occurring events. Below is a table of physical testing requirements that must be met to ensure the quality, performance, and reliability of Ideal Tridon no-hub coupling products.

TEST	GASKET PHYSICAL TESTING - MINIMUM OR MAXIMUM REQUIREMENTS		ASTM METHOD
<b>Tensile Strength Elongation Durometer</b>	Tests performed on new samples at room temperature (76°F ± 5°F)	1500 psi minimum 250% elongation before break 70 ± 5 points	D412: @ 20 in/min D412: @ 20 in/min D2240: Shore A
<b>Tensile Strength Elongation Durometer</b>	Heat-aged sample testing Test after heat aging for 96 hr @ 158°F (± 2°)	No greater than a 15% loss in strength No greater than a 20% loss in elongation before break No greater than a 10-point increase in hardness	D573
<b>Compression Set</b>	Test after heat aging for 22 hr @ 158°F (± 2°) at an induced deflection of 25%	25% maximum compression set after 30-minute recovery	D395: Method B
<b>Oil Immersion</b>	Test after immersion in IRM 903 oil for 70 hr (± 0.7 hr) @ 212°F (± 2°)	80% maximum allowable volume increase	D471
<b>Ozone Cracking</b>	Test and inspect after 100 (± 1) hours exposure in 100 pphm ozone concentration at 104°F (± 2°) while loop mounted to induce approximately 20% elongation.	No visible cracking at 2x magnification of the gasket	D1149: Method B
<b>Tear Resistance</b>	Pull sample cut from die C into 2 pieces	No less than 150 pounds per inch of thickness before tearing	D624: Die C Cutout
<b>Water Absorption</b>	Test after immersion in distilled water for 7 days @ 158°F (± 2°)	20% maximum allowable weight increase	D471

## COUPLING PERFORMANCE

Ideal Tridon no-hub products are designed to meet or exceed specifications for couplings used in all drain, waste, and vent (DWV) hubless cast iron pipe systems. Examples include residential or commercial sanitary applications such as hospitals or large multi-level commercial buildings, or above- and below-ground stormwater piping systems. All Ideal Tridon Super Heavy-Duty Green Shield No-Hub Couplings are designed to be installed with a pre-set torque wrench calibrated at 80 inch-pounds to accommodate the all 300 series stainless steel 3/8" hex-head/shoulder screw.

Coupling Meets <b>ASTM C1540</b>			Meets <b>FM1680</b>
Gasket Meets <b>ASTM C564</b>	IAPMO Listed File # 3198	Meets CSA B602	Meets Sealing Requirements <b>Independent Lab Certified</b>

## BRACING AND INSTALLATION

In applications using larger diameter pipes, it is required that adequate bracing be placed on the pipes to support the larger forces that can inherently act on the joints. Per the Cast Iron Soil Pipe and Fittings Handbook, published by the Cast Iron Soil Pipe Institute (CISPI), horizontal pipes and fittings larger than 5" nominal diameter shall be suitably braced to prevent horizontal movement. This shall be done at every branch opening or change of direction by the use of braces, blocks, rodding, or other suitable method, to prevent movement. Vertical components shall be secured at each stack base and at sufficiently close intervals to keep the system in alignment and to adequately support the pipe and its contents. Refer to local codes for specific requirements.